






Torque(N-m)



Connector A


A : Power Pin Assignment	
Signal	AMP-172168-1
U	3
V	2
W	1
≡	4
B+	5
B-	6



Connector B

B : Encoder Pin Assignment		
Function	Signal	AMP-1-172169-9
Power	5V	1
	0V	2
Serial Data Signal	SD +	7
	SD -	8
Shielding	Shielding	9

Rated Power : 200W
Drive Input Voltage : 220VAC
Rated Torque : 0.64N-m
Rated Speed : 3000 rpm
Rated Current : 1.6A(Arms)
Moment of Inertia : 0.33 Kg-m² (*10⁻⁴)
Encoder : 23-bit Incremental
Brake : Yes
Shaft : Key,Center tap
Oil seal : Yes



Key Size

ITEM	DATE	MODIFIED	DESCRIPTION	ECN NO.	CHK	APPD

NAME	DWG NO	SHEET	TYPE	EM1-C-M-20-2-B-E-0-D	DATE	2019.09.23
AC SERVO MOTOR	AC42419	A1	1-1	CUSTOMER	DRN	周孟儒
			SCALE	1 : X	CHK	何昆懋
			PART NO	FRE02202E008	APPD	黎振安

HIWIN® MIKROSYSTEM CORP.