






Torque(N·m)




| A : Power Pin Assignment |              |
|--------------------------|--------------|
| Signal                   | AMP-172167-1 |
| U                        | 3            |
| V                        | 2            |
| W                        | 1            |
| GND                      | 4            |

Rated Power : 200W  
 Drive Input Voltage : 220VAC  
 Rated Torque : 0.64N·m  
 Rated Speed : 3000 rpm  
 F Rated Current : 1.6A(Arms)  
 Moment of Inertia : 0.26 Kg·m<sup>2</sup>(\*10<sup>-4</sup>)  
 Encoder : 23-bit Incremental  
 Brake : No  
 Shaft : Key,Center tap  
 Oil seal : Yes



| B : Encoder Pin Assignment |           |                |
|----------------------------|-----------|----------------|
| Function                   | Signal    | AMP-1-172169-9 |
| Power                      | 5V        | 1              |
|                            | 0V        | 2              |
| Serial Data Signal         | SD +      | 7              |
|                            | SD -      | 8              |
| Shielding                  | Shielding | 9              |



| NAME           | DWG NO       | SHEET | TYPE  | EM1-C-M-20-2-0-E-0-D | DATE       |
|----------------|--------------|-------|-------|----------------------|------------|
| AC SERVO MOTOR | AC42415      | A1    | 1-1   |                      | 2019.09.23 |
| CUSTOMER       |              |       |       | DRN                  | 周孟儒        |
| SCALE          |              |       | 1 : X | CHK                  | 何昆懋        |
| PART NO        | FRE02202E004 |       |       | APPD                 | 黎振安        |

HIWIN® MIKROSYSTEM CORP.