






Torque(N-m)



Connector A

A : Power Pin Assignment		
Signal	AMP-172168-1	
U	3	
V	2	
W	1	
≡	4	
B+	5	
B-	6	



Connector B

B : Encoder Pin Assignment			
Function	Signal		AMP 1-172169-9
Power	5V		1
	0V		2
Serial data	SD	+	7
	SD	-	8
Shielding	Shielding		9
Battery	VB		5
	GND		6

Rated Power : 200W  
Drive Input Voltage : 220VAC  
Rated Torque : 0.64N-m  
Rated Speed : 3000 rpm  
Rated Current : 1.6A(Arms)  
Moment of Inertia : 0.33 Kg-m<sup>2</sup> (\*10<sup>-4</sup>)  
Encoder : 23-bit Absolute  
Brake : Yes  
Shaft : Round  
Oil seal : Yes

ITEM	DATE	MODIFIED	DESCRIPTION	ECN NO.	CHK	APPD

NAME	DWG NO	SHEET	TYPE	EM1-C-M-20-2-B-F-0-B	DATE	2019.09.23
AC SERVO MOTOR	AC42409	A1	1-1	CUSTOMER	DRN	周孟儒
HIWIN® MIKROSYSTEM CORP.			SCALE	1 : X	CHK	何昆懋
			PART NO	FRE02202F006	APPD	黎振安