




Torque(N-m)



Connector A

A : Power Pin Assignment	
Signal	AMP-172167-1
U	3
V	2
W	1
≡	4



Connector B

B : Encoder Pin Assignment			
Function	Signal		AMP-1-172169-9
Power	5V		1
	0V		2
Serial Data Signal	SD	+	7
	SD	-	8
Shielding	Shielding		9

Rated Power : 400W  
Drive Input Voltage : 220VAC  
Rated Torque : 1.27N-m  
Rated Speed : 3000 rpm  
Rated Current : 2.5A(Arms)  
Moment of Inertia : 0.48 Kg-m<sup>2</sup> (\*10<sup>-4</sup>)  
Encoder : 23-bit Incremental  
Brake : No  
Shaft : Round  
Oil seal : Yes

ITEM	DATE	MODIFIED	DESCRIPTION	ECN NO.	CHK	APPD

NAME	DWG NO	SHEET	TYPE	EM1-C-M-40-2-0-E-0-B	DATE	2019.09.03
AC SERVO MOTOR	AC42397	A1	1-1	CUSTOMER	DRN	周孟儒
HIWIN® MIKROSYSTEM CORP.			SCALE	1 : X	CHK	何昆懋
			PART NO	FRE02402E002	APPD	黎振安