



Connector A


A : Power Pin Assignment		
Signal	AMP-172167-1	
U	3	
V	2	
W	1	
≡	4	



Connector B

B : Encoder Pin Assignment			
Function	Signal		AMP 1-172169-9
Power	5V		1
	0V		2
Serial data Signal	SD	+	7
	SD	-	8
Shielding	Shielding		9
Battery	VB		5
	GND		6

Rated Power : 400W
Drive Input Voltage : 220VAC
Rated Torque : 1.27N-m
Rated Speed : 3000 rpm
Rated Current : 2.5A(Arms)
Moment of Inertia : 0.48 Kg-m² (*10⁻⁴)
Encoder : 23-bit Absolute
Brake : No
Shaft : Key,Center tap
Oil seal : Yes



Key Size

ITEM	DATE	MODIFIED	DESCRIPTION	ECN NO.	CHK	APPD

NAME	DWG NO	SHEET	TYPE	EM1-C-M-40-2-0-F-0-D	DATE	2019.08.05
AC SERVO MOTOR	AC42387	A1	1-1	CUSTOMER	DRN	周孟儒
HIWIN® MIKROSYSTEM CORP.				SCALE	1 : X	CHK 何昆懋
				PART NO	FRE02402F004	APPD 黎振安