


A : Power Pin Assignment	
Signal	AMP-172168-1
U	3
V	2
W	1
≡	4
B+	5
B-	6



B : Encoder Pin Assignment		
Function	Signal	AMP 1-172169-9
Power	5V	1
	0V	2
Serial data	SD +	7
	SD -	8
Shielding	Shielding	9
Battery	VB	5
	GND	6

Rated Power : 400W  
Drive Input Voltage : 220VAC  
Rated Torque : 1.27N-m  
Rated Speed : 3000 rpm  
Rated Current : 2.5A(Arms)  
Moment of Inertia : 0.49 Kg-m<sup>2</sup> (\*10<sup>-4</sup>)  
Encoder : 23-bit Absolute  
Brake : Yes  
Shaft : Round  
Oil seal : Yes

ITEM	DATE	MODIFIED	DESCRIPTION	ECN NO.	CHK	APPD

NAME	DWG NO	SHEET	TYPE	EM1-C-M-40-2-B-F-0-B	DATE	2019.08.05
AC SERVO MOTOR	AC42391	A1	1-1	CUSTOMER	DRN	周孟儒
HIWIN® MIKROSYSTEM CORP.			SCALE	1 : X	CHK	何昆懋
			PART NO	FRE02402F006	APPD	黎振安