






1 2 3 4 5 6 7 8 9




Torque(N·m)



Power Pin Assignment	
Signal	AMP-172168-1
U	3
V	2
W	1
±	4
B+	5
B-	6



Rate Power : 100W
 Driver Input Voltage : 220V
 Rated Torque : 0.32N·m
 Rated Speed : 3000 rpm
 Rated Current : 0.9A(Arms)
 Encoder : DA-235-17(HIWIN 17-bit Incremental)
 Brake : Yes
 Shaft : Key,Center tap
 Oil seal : No



BREAK SHARP EDGE UNLESS OTHER SPECIFIED

ROUGH M/C		FIT M/C		GRD		TOLERANCE mm		TYPE/ CUSTOMER	NAME	MATERIAL	MODEL	DWG.NO	SCALE	
UP	TO	6	30	120	300	600	1200	OVER	DATE	DRN	CHK			
6.3a		1.6a		0.4a					2014.03.15	邱婉容	鄭立巍	0100	AC02052A2	1-1
												APPD	Hsin-An	

ITEM	DATE	MODIFIED	DESCRIPTION	APPROVED
⚠ 2014.05.23	邱婉容	新增尺寸21.5	U120B-ECN-140509	

FRLS102B6A4C

HIWIN® MIKROSYSTEM CORP.