




Torque(N-m)




Brake Pin Assignment	
Signal	WPS3102A14S-7P-R
B+	A
B-	C

Connector C




Power Pin Assignment	
Signal	WPS3102A18-10P-R
U	A
V	B
W	C
⏏	D

Connector A



Encoder Pin Assignment		
Function	Signal	WPS3102A18-1P-R
Power	5V	A
	0V	B
Incremental Signal	SL +	C
	SL -	D
	TBD -	E
	TBD -	F
	MA +	G
	MA -	H
Shielding	Shielding	I

Connector B



Key Size

Rate Power : 2000W
 Driver Input Voltage : 220V
 Rated Torque : 9.55N-m
 Rated Speed : 2000 rpm
 Rated Current : 11A(Arms)
 Encoder : DA-235-17(HIWIN 17-bit Incremental)
 Brake : Yes
 Shaft : Key, Center tap
 Oil seal : No

1	2014.07.02	邱婉容	新增尺寸50	U120B-ECN-140407
ITEM	DATE	MODIFIED	DESCRIPTION	APPD

NAME	DWG NO	SHEET	TYPE	MM2KW	DATE	2014.03.15
AC SERVO MOTOR	AC32019	A2	1-1	CUSTOMER	DRN	邱婉容
HIWIN ® MIKROSYSTEM CORP.				SCALE	1 : X	CHK 鄭立巍
				PART NO	FRMM2K2B613C	APPD 江新安