





HIWIN CONFIDENTIAL

機密文件未經許可，嚴禁複製




Torque(N·m)




Brake Pin Assignment	
Signal	WPS3102A14S-7P-R
B+	A
B-	C

Connector C



Power Pin Assignment	
Signal	WPS3102A18-10P-R
U	A
V	B
W	C
⏏	D

Connector A



Encoder Pin Assignment			
Function	Signal		WPS3102A18-1P-R
Power	5V		A
	0V		B
Incremental Signal	SL	+	C
	SL	-	D
	TBD	--	E
	TBD	--	F
	MA	+	G
	MA	-	H
Shielding	Shielding		I

Connector B

Rate Power : 2000W

Driver Input Voltage : 220V

Rated Torque : 9.55N·m

Rated Speed : 2000 rpm

Rated Current : 11A(Arms)

Encoder : DA-235-17(HIWIN 17-bit Incremental)

Brake : Yes

Shaft : Round

Oil seal : No

1	2014.07.02	邱婉容	新增尺寸50	U120B-ECN-140407
ITEM	DATE	MODIFIED	DESCRIPTION	APPD

NAME	DWG NO	SHEET	TYPE	MM2KW	DATE	2014.03.15
AC SERVO MOTOR	AC32015	A2	1-1	CUSTOMER	DRN	邱婉容
HIWIN® MIKROSYSTEM CORP.				SCALE	1 : X	CHK 鄭立巍
				PART NO	FRMM2K2B613A	APPD 江新安