




Torque(N-m)



Connector A

A : Power Pin Assignment	
Signal	AMP-172167-1
U	3
V	2
W	1
\equiv	4



Connector B

B : Encoder Pin Assignment		
Function	Signal	AMP 1-172169-9
Power	5V	1
	0V	2
Incremental Signal	SD +	7
	SD -	8
Shielding	Shielding	9
Battery	VB	5
	GND	6

Rate Power : 750W
Driver Input Voltage : 220V
Rated Torque : 2.4N-m
Rated Speed : 3000 rpm
Rated Current : 5.1A(Arms)
Moment of Inertia : 1.4 Kg-m² (*10⁻⁴)
Allowable Load Inertia Ratio : 10 times or less
Encoder : 17-bit Absolute
Brake : No
Shaft : Round
Oil seal : Yes

NAME	DWG NO	SHEET	TYPE	MS750W	DATE	2015.01.13
AC SERVO MOTOR	AC22053	A3	1-1	CUSTOMER	DRN	邱婉容
HIWIN ® MIKROSYSTEM CORP.				SCALE	1 : X	CHK 鄭立巍
				PART NO	FRMS7520408B	APPD 江新安

ITEM	DATE	MODIFIED	DESCRIPTION	CHK	APPD
2	2018.08.20	周孟儒	U1000-ECN-180807 更換為含油封前蓋	林政穎	鄭立巍
1	2018.05.02	周孟儒	U1000-ECN-180501	林政穎	鄭立巍