



**Customer sign**

**(表B-近接開關腳位表)**

Motor wiring diagram	
Signal	Color
V	Black-2
U	Black-1
W	Black-3
GND	Green/Yellow
T+	Black-5
T-	Black-6
Shield	

**(表C-馬達腳位表)**

**註 :**

- 規格: LMSSA-20S700-2-□□□□(行程)-□(讀頭)□(出線).3□(近接開關)-S-S-A0.
- (規格編碼原則請參閱型錄)
- 移動部重量: 13.5kg, 連續推力: 725 N, 瞬間推力: 2048N .
- HIWIN 精度保證於室溫23°C±1°C下量測.
- 出貨時鎖附在花崗岩上進行量測.
- 若未搭配 HIWIN 驅動器 , 出貨報告只提供精度補償表.
- 讀頭延長線需另外購買.
- 此圖面尺寸不適合用於霍爾編碼器

**(表D-讀頭腳位表)**

Positioning Measurement-Digital					
Function	Signal	Color	D-Sub (Male-15P) optical	magnetic	
Power	5V	Brown	7,8	7	
	0V	White	2,9	2	
Incremental signals	A+	Green	14		
	A-	Yellow	6		
	B+	Blue	13		
	B-	Red	5		
Reference mark	Z+	Violet	12		
	Z-	Grey	4		
Shield	Inner	Inner Shield	15	case	
	Outer	Outer Shield	case	-	