


Jumper 1/4SF LSOH 7/16 Din Male Elbow – 7/16 Din Female Bulkhead

ASTB-202X

Description

Cable:	ACOME 50-1/4SF LSOH cable
Connector:	7/16 Din male elbow / 7/16 Din Female Bulkhead
Assembly:	Inner and outer contact 100% soldered and with thermal shrink tube



Electrical Characteristics

Impedance:	50 ± 1Ω	
Operating Frequency Range:	DC ~ 3GHz	
RMS Power (40 °C - 2 GHz):	0.35 KW	
Velocity:	83%	
Passive Intermodulation Measured In Swept Frequency Mode, With 2 × 20W Carriers:	IM3 at 900MHz	≤ -150 dBc
	IM3 at 1800MHz	≤ -150 dBc
	IM7 at 2100MHz	≤ -150 dBc

Mechanical Characteristics

Material and Finish of Connector Body:	Copper alloy - plated brass
Material and Finish of Coupling Nut:	Nickel - plated brass
Material and Finish of Inner Conductor:	Silver - plated bronze
Coupling Waterproof:	Silicone Rubber O-ring
Coupling Torque:	30 N.m Max.
Minimum Bending Radius:	25 mm

Environmental Characteristics

Temperature:	Operating	-40 °C / +70 °C
	Installation	-25 °C / +55 °C
	Storage	-50 °C / +70 °C
Waterproof Index:	IP68 (1m /24 h)	
RoHS Compliance:	Yes	
Test -40Methods:	IEC 61169, IEC 62037, IEC 60529	

Length (m)	Product number	Frequency 0/1000MHz		Frequency 1000/2200MHz		Frequency 2200/3000MHz	
		RL (dB)	ATT (dB)	RL (dB)	ATT (dB)	RL (dB)	ATT (dB)
0.9	C2238X	-28	0.32	-26	0.49	-24	0.57