

Jumper 3/8SF PE N Male -N Female

ASTB-C4286X

Description

| | |
|-------------------|--------------------------------------------------------------------|
| Cable: | ACOME 50-3/8SF PE cable M5458 |
| Connector: | N female / N male |
| Assembly: | Inner and outer contact 100% soldered and with thermal shrink tube |

Electrical Characteristics

| | |
|----------------------------------------------------------------------------------------|-------------------------------------------|
| Impedance: | 50 ± 1Ω |
| Operating Frequency Range: | DC ~ 3GHz |
| RMS Power (40 °C - 2 GHz): | 0.35 KW |
| Velocity: | 82% |
| Passive Intermodulation Measured In Swept Frequency Mode, With 2 × 20W Carries: | Dynamic: ≤ -150 dBc Static: ≤ -160 dBc |

Mechanical Characteristics

| | |
|------------------------------------------------|-----------------------------|
| Material and Finish of Connector Body: | Copper alloy - plated brass |
| Material and Finish of Coupling Nut: | Nickel - plated brass |
| Material and Finish of Inner Conductor: | Silver - plated bronze |
| Coupling Waterproof: | Silicone Rubber O-ring |
| Coupling Torque: | 2.5 N.m Max. |
| Minimum Bending Radius: | 25 mm |

Environmental Characteristics

| | | |
|--------------------------|----------------------|-----------------|
| Temperature: | Operating | -55 °C / +70 °C |
| | Installation | -25 °C / +55 °C |
| | Storage | -50 °C / +70 °C |
| Waterproof Index: | IP68 (1m /24 h) | |
| RoHS Compliance: | Yes | |
| Test Methods: | IEC 61169, IEC 60529 | |

| Length (m) | Product number | Frequency 0/1000MHz | | Frequency 1000/2200MHz | | Frequency 2200/3000MHz | |
|------------|----------------|---------------------|----------|------------------------|----------|------------------------|----------|
| | | RL (dB) | ATT (dB) | RL (dB) | ATT (dB) | RL (dB) | ATT (dB) |
| 1 | C4286X-L100 | -28 | 0.25 | -26 | 0.39 | -24 | 0.46 |
| 1.25 | C4286X-L125 | -28 | 0.29 | -26 | 0.44 | -24 | 0.52 |
| 2 | C4286X-L200 | -28 | 0.39 | -26 | 0.61 | -24 | 0.72 |
| 2.5 | C4286X-L250 | -28 | 0.46 | -26 | 0.72 | -24 | 0.85 |