

Certificate of Suitability

Global-Mark Pty. Ltd., certify the electrical equipment described hereunder complies with standards listed herein and notifies the certificate holder to affix the Regulatory Compliance Mark (RCM) mark to products of the same type provided that the requirements of all relevant parts of AS/NZS 4417 applicable to the article are fulfilled. In placing the RCM mark on the product, the Responsible Supplier makes a declaration of compliance with the certification standard(s) and confirms that the product is identical to the product certified herein. – **This Certificate meets the requirements of a Recognised External Certification Scheme (RECS) including the rules of the EESS.**

CERTIFICATION AND CERTIFICATE HOLDER DETAILS

Company Name	Lifud Technology Co.,Ltd		
Address	(1/F-3/F, Building F, Kutto Industrial Park) 1/F-3/F, Building B, No.26 Xinhe Road, Xinqiao Community, Xinqiao Street Bao'an District Shenzhen Guangdong 518104 China		
Client ID	105301	Global-Mark File Number:	105301-023
Certification Number	GMA-508117	Revision Number	00
Certificate Standard(s)	AS 61347.2.13:2018 Lamp Control Gear - Part 2-13: Particular Requirements For D.C Or A.C Supplied Electronic Control Gear For Led Modules.		
Type of Certification	Electrical Safety Product <i>Scheme</i>	Global-Mark Electrical Product Safety Certification Scheme	
			System 1 Approval

CERTIFICATE DATES

Certificate Issue Date	2/09/2020
Certificate Last Update Date	
Certification Expiry Date	2/09/2025

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Suitability

CERTIFIED ELECTRICAL EQUIPMENT				
Declared Article	Product Description	Trade Name	Model Number	Rating
Non declared	LED Driver	LIFUD	LF-GLD025YE0250H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 250mA, 10.50W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0255H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 255mA, 10.71W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0260H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 260mA, 10.92W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0265H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 265mA, 11.13W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0270H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 270mA, 11.34W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0275H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 275mA, 11.55W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0280H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 280mA, 11.76W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0285H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 285mA, 11.97W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0290H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 290mA, 12.18W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD025YE0295H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 295mA, 12.39W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0300H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 300mA, 12.60W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0305H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 305mA, 12.81W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0310H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 310mA, 13.02W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0315H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 315mA, 13.23W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0320H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 320mA, 13.44W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0325H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 325mA, 13.65W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0330H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 330mA, 13.86W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0335H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 335mA, 14.07W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0340H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 340mA, 14.28W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD025YE0345H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 345mA, 14.49W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0350H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 350mA, 14.70W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0355H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 355mA, 14.91W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0360H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 360mA, 15.12W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0365H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 365mA, 15.33W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0370H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 370mA, 15.54W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0375H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 375mA, 15.75W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0380H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 380mA, 15.96W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0385H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 385mA, 16.17W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0390H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 390mA, 16.38W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD025YE0395H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 395mA, 16.59W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0400H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 400mA, 16.80W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0405H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 405mA, 17.01W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0410H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 410mA, 17.22W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0415H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 415mA, 17.43W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0420H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 420mA, 17.64W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0425H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 425mA, 17.85W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0430H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 430mA, 18.06W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0435H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 435mA, 18.27W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0440H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 440mA, 18.48W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD025YE0445H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 445mA, 18.69W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0450H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 450mA, 18.90W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0455H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 455mA, 19.11W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0460H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 460mA, 19.32W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0465H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 465mA, 19.53W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0470H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 470mA, 19.74W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0475H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 475mA, 19.95W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0480H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 480mA, 20.16W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0485H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 485mA, 20.37W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0490H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 490mA, 20.58W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD025YE0495H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 495mA, 20.79W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0500H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 500mA, 21.00W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0505H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 505mA, 21.21W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0510H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 510mA, 21.42W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0515H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 515mA, 21.63W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0520H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 520mA, 21.84W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0525H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 525mA, 22.05WW, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0530H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 530mA, 22.26W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0535H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 535mA, 22.47W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0540H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 540mA, 22.68W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD025YE0545H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 545mA, 22.89WW, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD025YE0550H	Input: 220-240VAC, 50/60Hz, Max.0.15A Output: 25-42Vdc, 550mA, 23.10W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD035YE0600H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 600mA, 25.20W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0605H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 605mA, 25.41W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0610H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 610mA, 25.62W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0615H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 615mA, 25.83W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0620H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 620mA, 26.04W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0625H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 625mA, 26.25W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0630H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 630mA, 26.46W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0635H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 635mA, 26.67W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD035YE0640H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 640mA, 26.88W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0645H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 645mA, 27.09W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0650H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 650mA, 27.30W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0655H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 655mA, 27.51W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0660H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 660mA, 27.72W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0665H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 665mA, 27.93W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0670H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 670mA, 28.14W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0675H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 675mA, 28.35W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0680H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 680mA, 28.56W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0685H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 685mA, 28.77W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD035YE0690H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 690mA, 28.98W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0695H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 695mA, 29.19W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0700H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 700mA, 29.40W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0705H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 705mA, 29.61W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0710H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 710mA, 29.82W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0715H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 715mA, 30.03W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0720H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 720mA, 30.24W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0725H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 725mA, 30.45W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0730H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 730mA, 30.66W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0735H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 735mA, 30.87W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD035YE0740H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 740mA, 31.08W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0745H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 745mA, 31.29W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0750H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 750mA, 31.50W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0755H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 755mA, 31.71W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0760H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 760mA, 31.92W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0765H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 765mA, 32.13W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0770H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 770mA, 32.34W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0775H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 775mA, 32.55W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0780H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 780mA, 32.76W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0785H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 785mA, 32.97W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD035YE0790H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 790mA, 33.18W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0795H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 795mA, 33.39W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD035YE0800H	Input: 220-240VAC, 50/60Hz, Max.0.2A Output: 25-42Vdc, 800mA, 33.60W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0850H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 850mA, 35.70W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0855H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 855mA, 35.91W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0860H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 860mA, 36.12W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0865H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 865mA, 36.33W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0870H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 870mA, 36.54W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0875H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 875mA, 36.75W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0880H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 880mA, 36.96W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD045YE0885H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 885mA, 37.17W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0890H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 890mA, 37.38W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0895H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 895mA, 37.59W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0900H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 900mA, 37.80W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0905H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 905mA, 38.01W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0910H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 910mA, 38.22W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0915H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 915mA, 38.43W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0920H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 920mA, 38.64W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0925H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 925mA, 38.85W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0930H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 930mA, 39.06W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD045YE0935H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 935mA, 39.27W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0940H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 940mA, 39.48W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0945H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 945mA, 39.69W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0950H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 950mA, 39.90W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0955H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 955mA, 40.11W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0960H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 960mA, 40.32W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0965H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 965mA, 40.53W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0970H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 970mA, 40.74W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0975H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 975mA, 40.95W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0980H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 980mA, 41.16W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD045YE0985H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 985mA, 41.37W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0990H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 990mA, 41.58W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE0995H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 995mA, 41.79W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE1000H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 1000mA, 42.00W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE1005H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 1005mA, 42.21W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE1010H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 1010mA, 42.42W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE1015H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 1015mA, 42.63W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE1020H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 1020mA, 42.84W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE1025H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 1025mA, 43.05W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE1030H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 1030mA, 43.26W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD045YE1035H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 1035mA, 43.47W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE1040H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 1040mA, 43.68W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE1045H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 1045mA, 43.89W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD045YE1050H	Input: 220-240VAC, 50/60Hz, Max.0.3A Output: 25-42Vdc, 1050mA, 44.10W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in
Non declared	LED Driver	LIFUD	LF-GLD055YE1100H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1100, 46.20W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1105H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1105, 46.41W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1110H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1110, 46.62W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1115H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1115, 46.83W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1120H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1120, 47.04W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1125H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1125, 47.25W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD055YE1130H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1130, 47.46W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1135H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1135, 47.67W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1140H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1140, 47.88W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1145H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1145, 48.09W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1150H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1150, 48.30W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1155H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1155, 48.51W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1160H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1160, 48.72W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1165H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1165, 48.93W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1170H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1170, 49.14W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1175H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1175, 49.35W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Global-Mark.com.au®



www.jas-anz.org/register

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD055YE1180H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1180, 49.56W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1185H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1185, 49.77W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1190H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1190, 49.98W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1195H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1195, 50.19W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1200H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1200, 50.40W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1205H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1205, 50.61W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1210H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1210, 50.82W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1215H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1215, 51.03W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1220H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1220, 51.24W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1225H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1225, 51.45W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD055YE1230H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1230, 51.66W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1235H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1235, 51.87W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1240H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1240, 52.08W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1245H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1245, 52.29W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1250H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1250, 52.50W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1255H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1255, 52.71W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1260H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1260, 52.92W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1265H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1265, 53.13W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1270H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1270, 53.34W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1275H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1275, 53.55W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD055YE1280H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1280, 53.76W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1285H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1285, 53.97W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1290H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1290, 54.18W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1295H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1295, 54.39W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD055YE1300H	Input: 220-240VAC, 50/60Hz, Max.0.35A Output: 25-42Vdc, 1300, 54.60W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1300H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1300mA, 54.60W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1305H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1305mA, 54.81W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1310H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1310mA, 55.02W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1315H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1315mA, 55.23W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1320H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1320mA, 55.44W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD065YE1325H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1325mA, 55.65W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1330H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1330mA, 55.86W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1335H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1335mA, 56.07W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1340H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1340mA, 56.28W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1345H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1345mA, 56.49W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1350H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1350mA, 56.70W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1355H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1355mA, 56.91W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1360H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1360mA, 57.12W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1365H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1365mA, 57.33W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1370H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1370mA, 57.54W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD065YE1375H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1375mA, 57.75W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1380H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1380mA, 57.96W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1385H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1385mA, 58.17W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1390H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1390mA, 58.38W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1395H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1395mA, 58.59W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1400H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1400mA, 58.80W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1405H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1405mA, 59.01W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1410H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1410mA, 59.22W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1415H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1415mA, 59.43W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1420H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1420mA, 59.64W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD065YE1425H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1425mA, 59.85W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1430H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1430mA, 60.06W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1435H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1435mA, 60.27W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1440H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1440mA, 60.48W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1445H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1445mA, 60.69W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1450H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1450mA, 60.90W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1455H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1455mA, 61.11W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1460H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1460mA, 61.32W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1465H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1465mA, 61.53W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1470H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1470mA, 61.74W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD065YE1475H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1475mA, 61.95W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1480H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1480mA, 62.16W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1485H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1485mA, 62.37W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1490H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1490mA, 62.58W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1495H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1495mA, 62.79W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD065YE1500H	Input: 220-240VAC, 50/60Hz, Max.0.40A Output: 25-42Vdc, 1500mA, 63.00W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in,
Non declared	LED Driver	LIFUD	LF-GLD080YE1550H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1550mA, 62.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1555H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1555mA, 62.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1560H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1560mA, 62.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1565H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1565mA, 62.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager






global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD080YE1570H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1570mA, 62.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1575H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1575mA, 63.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1580H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1580mA, 63.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1585H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1585mA, 63.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1590H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1590mA, 63.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1595H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1595mA, 63.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1600H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1600mA, 64.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1605H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1605mA, 64.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1610H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1610mA, 64.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1615H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1615mA, 64.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD080YE1620H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1620mA, 64.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1625H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1625mA, 65.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1630H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1630mA, 65.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1635H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1635mA, 65.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1640H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1640mA, 65.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1645H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1645mA, 65.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1650H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1650mA, 66.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1655H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1655mA, 66.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1660H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1660mA, 66.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1665H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1665mA, 66.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager






global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD080YE1670H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1670mA, 66.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1675H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1675mA, 67.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1680H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1680mA, 67.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1685H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1685mA, 67.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1690H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1690mA, 67.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1695H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1695mA, 67.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1700H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1700mA, 68.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1705H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1705mA, 68.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1710H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1710mA, 68.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1715H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1715mA, 68.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD080YE1720H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1720mA, 68.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1725H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1725mA, 69.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1730H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1730mA, 69.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1735H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1735mA, 69.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1740H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1740mA, 69.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1745H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1745mA, 69.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1750H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1750mA, 70.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1755H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1755mA, 70.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1760H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1760mA, 70.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1765H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1765mA, 70.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager






global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD080YE1770H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1770mA, 70.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1775H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1775mA, 71.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1780H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1780mA, 71.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1785H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1785mA, 71.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1790H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1790mA, 71.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1795H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1795mA, 71.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1800H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1800mA, 72.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1805H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1805mA, 72.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1810H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1810mA, 72.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1815H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1815mA, 72.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager





global-mark®

Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD080YE1820H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1820mA, 72.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1825H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1825mA, 73.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1830H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1830mA, 73.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1835H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1835mA, 73.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1840H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1840mA, 73.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1845H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1845mA, 73.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1850H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1850mA, 74.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1855H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1855mA, 74.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1860H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1860mA, 74.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1865H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1865mA, 74.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD080YE1870H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1870mA, 74.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1875H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1875mA, 75.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1880H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1880mA, 75.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1885H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1885mA, 75.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1890H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1890mA, 75.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1895H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1895mA, 75.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1900H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1900mA, 76.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1905H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1905mA, 76.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1910H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1910mA, 76.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1915H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1915mA, 76.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager




Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD080YE1920H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1920mA, 76.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1925H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1925mA, 77.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1930H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1930mA, 77.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1935H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1935mA, 77.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1940H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1940mA, 77.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1945H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1945mA, 77.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1950H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1950mA, 78.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1955H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1955mA, 78.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1960H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1960mA, 78.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1965H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1965mA, 78.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager




Certificate of Suitability

Non declared	LED Driver	LIFUD	LF-GLD080YE1970H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1970mA, 78.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1975H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1975mA, 79.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1980H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1980mA, 79.2W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1985H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1985mA, 79.4W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1990H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1990mA, 79.6W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE1995H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 1995mA, 79.8W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,
Non declared	LED Driver	LIFUD	LF-GLD080YE2000H	Input: 220-240VAC, 50/60Hz, Max.0.50A Output: 25-40Vdc, 2000mA, 80.0W, Uout(VDC): 55Vdc ta: 50°C, tc: 90°C, SELV Built-in ,

RELEVANT TRADEMARK (S)

COMMENTS OR CONDITIONS ON THE CERTIFICATION

LF-GLD025YExxxxx, LF-GLD035YExxxxx, LF-GLD045YExxxxx, LF-GLD055YExxxxx, LF-GLD065YExxxxx & LF-GLD080YExxxxx where:

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.


Certification Manager




global-mark®

Certificate of Suitability

'xxxx' denotes output current can be 0250 to 2000 representing 250mA to 2000mA, in steps of 5mA;
'y' can be A to Z which stands for series number]

End of document



This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager

Global-Mark Pty Ltd, Copyright 2012 - 407, 32 Delhi Road, North Ryde NSW 2113, Australia



Global-Mark.com.au®



WWW.JAS-ANZ.ORG/REGISTER