



Product Service

CERTIFICATE

No. U6 18 06 04006 032

Holder of Certificate: Lifud Technology Co., Ltd.

4&5/F, Bldg 14A
Taihua Wutong Island, Gushu Development Zone, Xixiang Street
Bao'an District
518126 Shenzhen
PEOPLE'S REPUBLIC OF CHINA

**Production
Facility(ies):**

93012

Certification Mark:**Product:****Power supplies
(LED Driver)****Model(s):**

LF-GMR020YSIlxxxxxy; LF-GMR030YSIlxxxxxy;
LF-GMR040YSIlxxxxxy; LF-GMR060YSIlxxxxxy;
LF-GMR080YSIlxxxxxy; LF-GSD045YB
["xxxx" can be 0200 to 2000 which stands for rated output
current (I_{rated}) 200mA to 2000mA, in steps of 5mA;
"y" can be A to Z which stands for series number]

Parameters:

Rated Input Voltage :	See page 2 for details
Rated Frequency :	50/60 Hz
Rated Input Current :	See page 2 for details
Rated Output :	See page 2 for details
Protection against Electric Shock :	SELV
Method of Installation:	Built-in
Type of Output :	Constant current type
to :	See page 2 for details

**Tested
according to:**

EN 61347-2-13:2014/A1:2017
EN 61347-1:2015
EN 62384:2006/A1:2009

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. The certification mark must not be altered in any way. See also notes overleaf.

Test report no.: 64142185006101**Date,** 2018-06-29

(Taylor Yao)



Page 1 of 2

Attestation of Conformity No. U6 18 06 04006 032



Product Service

Model No.	Rated Input Voltage (VAC)	Rated Input Current (A)	Output Voltage (VDC)	I _{rated} (mA)	U _{out} (VDC)	P _{rated} (W)	t _c (°C)
LF-GMR020YS II xxxxy	220-240	0.14	33-42	200-550	55	8.4-23.1	70
LF-GMR030YS II xxxxy		0.2	33-42	600-780	55	25.2-32.7	80
LF-GMR040YS II xxxxy		0.26	33-42	750-1050	55	31.5-44.1	85
LF-GMR060YS II xxxxy		0.4	33-42	1100-1550	55	46.2-65.1	85
LF-GMR080YS II xxxxy		0.5	33-42	1600-2000	55	67.2-84.0	90
LF-GSD045YB	100-240	0.6	25-42	800	50	33.6	90
				850		35.7	
				900		37.8	
				950		39.9	
				1000		42.0	
				1050		44.1	
Remark: "xxxx" can be 0200 to 2000 which stands for rated output current (I _{rated}) 200mA to 2000mA, in steps of 5mA; "y" can be A to Z which stands for series number.							