


STANDARD JOYSTICK MJ-4K



Use of contactless Hall technology in the joystick is suitable if limited installation space is available or the application is subject to high vibration. The MJ-4K 2-axis joystick fulfills these requirements to a high rate. The trusted durability of the MJ-xx joystick series is also guaranteed with the MJ-4K.

The applications are extensive and range from rehabilitation engineering and automation technology to construction equipment and marine applications.



ELECTRICAL SPECIFICATIONS

Operational voltage	5 V \pm 0,5 V
Output signal	0,5 ... 4,5 V
Linearity	\pm 3%
Deflection angle, el.	\pm 19°
Power consumption	< 20 mA
Max. output current	\pm 8 mA
Resolution	16 bit
Option	Redundant output signal
Electrostatic discharge	BS EN 61000-4-2
Radio interference	BS EN 61000-4-3
High-frequency interfering signals	BS EN 61000-4-4
Conducted interfering signals	BS EN 61000-4-6
Radiated emission	EN 55016-2-3:2010+A1:2010

Specifications are subject to change without notice.
* Other values on request.

MECHANICAL SPECIFICATIONS

Service life	5 million cycles
Deflection angle, mech.	\pm 19°
Operating force	3,5 N typically *
Gate shape	Circular
Centre position tolerance	\pm 1°
Impact strength	100 N

ELECTRICAL CONNECTION

FCI Minitek 98414

AMBIENT CONDITIONS

Storage temperature	-40°C ... +85°C
Operating temperature	-25 ... 70°C (opt. -40 ... 85°C)
Protection class (above mounting flange)	IP 65

MATERIALS

Base	Aluminium
Bearing	Stainless steel/plastic

MJ-4K

Type	MJ-4K XY: Hall 0,5...4,5V
Item number	E060200408 (2-axis)

DRAWINGS FOR MJ-4K

