AT1045K

100V N-Channel MOSFET

Features

- Advanced high cell density Trench technology
- Super Low Gate Charge
- Excellent CdV/dt effect decline
- 100% EAS Guaranteed
- Green Device Available

Product Summary

V_{DS}	100	V
I_D	45	A
$R_{DS(ON)}$ (at V_{GS}=10V)	22	mΩ

Applications

- High Frequency Point-of-Load Synchronous Buck Converter
- Networking DC-DC Power System
- LED TV Back Light



TO-252 Top View



Absolute Maximum Ratings(T_C=25℃, unless otherwise noted)

Parameter	Symbol	Rating	Units
Drain-Source Voltage	V_{DS}	100	V
Gate-Source Voltage	V_{GS}	±20	V
Continuous Drain Current, VGS @ 10V[1]	I_D@T_C=25℃	45	A
Continuous Drain Current, VGS @ 10V[1]	I_D@T_C=100℃	28	A
Pulsed Drain Current[2]	I_{DM}	100	A
Single Pulse Avalanche Energy[3]	EAS	84	mJ
Avalanche Current	I_{AS}	41	A
Total Power Dissipation[4]	P_D@T_C=25℃	90	W
Storage Temperature Range	T_{STG}	-55 to 150	℃
Operating Junction Temperature Range	T_J	-55 to 150	℃

Thermal Characteristics

Parameter	Symbol	Typ	Max	Unit
Thermal Resistance Junction-Ambient[1]	$R_{\theta JA}$	---	62	℃/W
Thermal Resistance Junction-Case[1]	$R_{\theta JC}$	---	1.4	℃/W

Electrical Characteristics (T_J=25℃, unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V , I_D=250uA	100	---	---	V
BV_{DSS} Temperature Coefficient	$\triangle BV_{DSS}/\triangle T_J$	Reference to 25℃ , I_D=1mA	---	0.096	---	V/℃
Static Drain-Source On-Resistance[2]	$R_{DS(ON)}$	V_{GS}=10V , I_D=30A	---	18	22	mΩ
Gate Threshold Voltage	$V_{GS(th)}$	V_{GS}=V_{DS} , I_D =250uA	2.5	---	4.5	V
$V_{GS(th)}$ Temperature Coefficient	$\triangle V_{GS(th)}$		---	-5.5	---	mV/℃
Drain-Source Leakage Current	I_{DSS}	V_{DS}=80V , V_{GS}=0V , T_J=25℃	---	---	1	uA
		V_{DS}=80V , V_{GS}=0V , T_J=55℃	---	---	5	
Gate-Source Leakage Current	I_{GSS}	V_{GS}=±20V , V_{DS}=0V	---	---	±100	nA
Forward Transconductance	gfs	V_{DS}=5V , I_D=30A	---	27	---	S
Gate Resistance	R_g	V_{DS}=0V , V_{GS}=0V , f=1MHz	---	1.9	3.8	Ω
Total Gate Charge (10V)	Q_g	V_{DS}=80V , V_{GS}=10V , I_D=30A	---	27.6	38.6	nC
Gate-Source Charge	Q_{gs}		---	11.4	16	
Gate-Drain Charge	Q_{gd}		---	7.9	11.1	
Turn-On Delay Time	$T_{d(on)}$	V_{DD}=50V , V_{GS}=10V , R_G=3.3Ω, I_D=30A	---	15.6	31.2	ns
Rise Time	T_r		---	17.2	31	
Turn-Off Delay Time	$T_{d(off)}$		---	16.8	33.6	
Fall Time	T_f		---	9.2	18.4	
Input Capacitance	C_{iss}	V_{DS}=15V , V_{GS}=0V , f=1MHz	---	1890	2645	pF
Output Capacitance	C_{oss}		---	268	375	
Reverse Transfer Capacitance	C_{rss}		---	67	94	

Drain-Source Diode Characteristics

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Continuous Source Current[1,5]	I_S	V_G=V_D=0V , Force Current	---	---	45	A
Pulsed Source Current[2,5]	I_{SM}		---	---	100	A
Diode Forward Voltage[2]	V_{SD}	V_{GS}=0V , I_S=1A , T_J=25℃	---	---	1.2	V
Reverse Recovery Time	t_{rr}	I_F=30A ,di/dt=100A/μs, T_J=25℃	---	34	---	nS
Reverse Recovery Charge	Q_{rr}		---	47	---	nC

Note:

1.The data tested by surface mounted on a 1 inch^2 FR-4 board with 2OZ copper.

2.The data tested by pulsed , pulse width ≦ 300us , duty cycle ≦ 2%

3.The EAS data shows Max. rating . The test condition is V_{DS}=25V,V_{GS}=10V,L=0.1mH,I_{AS}=41A

4.The power dissipation is limited by 150℃ junction temperature

5.The data is theoretically the same as I_D and I_{DM} , in real applications , should be limited by total power dissipation.

Typical Characteristics



Fig.1 Typical Output Characteristics



Fig.2 On-Resistance v.s Gate-Source



Fig.3 Forward Characteristics of Reverse



Fig.4 Gate-Charge Characteristics



Fig.5 Normalized $V_{GS(th)}$ v.s T_J



Fig.6 Normalized R_{DSON} v.s T_J



Fig.7 Capacitance



Fig.8 Safe Operating Area



Fig.9 Normalized Maximum Transient Thermal Impedance



Fig.10 Switching Time Waveform



Fig.11 Unclamped Inductive Switching Waveform

TO-252 Package Outline Dimensions



Symbol	Dimensions (unit:mm)			Symbol	Dimensions (unit:mm)		
	Min	Typ	Max		Min	Typ	Max
A	2.20	2.30	2.38	**E_1**	4.40	--	--
A_1	0.46	0.50	0.63	**e**	2.286 BSC		
b	0.64	0.76	0.89	**e_1**	--	4.57	--
b_1	0.77	0.85	1.14	**H_D**	9.40	10.00	10.40
b_2	5.00	5.33	5.46	**L**	2.743 REF		
c	0.458	0.508	0.558	**L_1**	1.40	1.52	1.77
D_1	5.98	6.10	6.223	**L_2**	0.50	0.80	1.01
D_2	5.21	--	--	**W**	--	0.20	--
E	6.40	6.60	6.731	**y**	--	--	0.20