



DETAIL DOTS
SCALE: 10:1



DETAIL B BACK VIEW
SCALE: 2:1



PIN	NAME	PIN	NAME
1	/CS1	15	VSS
2	/RES	16	VOUT
3	A0	17	CAP3+
4	/WR	18	CAP1-
5	/RD	19	CAP1+
6	D0	20	CAP2+
7	D1	21	CAP2-
8	D2	22	V1
9	D3	23	V2
10	D4	24	V3
11	D5	25	V4
12	D6	26	V0
13	D7	27	LC0-ID
14	VDD	28	TRS

SPECIFICATIONS

1. DISPLAY TYPE: FST/TRANSFLECTIVE/POSITIVE/B-W
2. LCD DRIVING VOLTAGE: 9.0 V
3. LOGIC VOLTAGE: 3.0 V
4. VIEWING DIRECTION: 6 O'CLOCK
5. OPERATING TEMP: -10° C -- +50° C
6. STORAGE TEMP: -20° C -- +60° C
7. DRIVE MODE: 1/6S DUTY, 1/9 BIAS
8. BACKLIGHT: WHITE/SIDE BACKLIGHT 3.1V

NOTE:

Molex connector (50-37-5023) or equivalent

DESCRIPTION:

C/D

SCALE: FIT
SHEET: IOF 1
MODEL: T12864-C0632
INDUSTRIAL CO., LTD.



UNIT: mm
PROJECTION
DATE: DATE: DATE: DATE: SERIAL NUMBER

APP: APP: APP: APP: CHK: CHK: CHK: CHK: DWN: DWN: DWN: DWN: DATE: DATE: DATE: DATE: DATE: DATE: DATE: DATE: SERIAL NUMBER