

iq.ul.com

PROSPECTOR®

CLICK TO CONTINUE

The information is provided for informational purposes only. It is not intended to be used as a substitute for the information provided by the material supplier. The information is provided for informational purposes only. It is not intended to be used as a substitute for the information provided by the material supplier.

View additional material information including performance and processing data

是否将当前网页翻译成中文

网页翻译

中英对照

关闭

Component - Plastics

Guide Information

E67171

**LG CHEM LTD**  
128 Yeoui-daero Yeongdeungpo-gu, Seoul 07336 KR

**TR552**  
Acrylonitrile Butadiene Styrene/Methyl Methacrylate (ABS/MMA), furnished as pellets

Color	Min. Thk (mm)	Flame Class	HWI	HA1	RTI Elec	RTI Imp	RTI Str
ALL	1.5	HB	-	-	50	50	50
	3.0	HB	-	-	50	50	50


Comparative Tracking Index (CTI): -  
Dielectric Strength (kV/mm): -  
High-Voltage Arc Tracking Rate (HVTR): -  
Dimensional Stability (%): -

Inclined Plane Tracking (IPT) kV: -  
Volume Resistivity (10<sup>x</sup> ohm-cm): -  
Surface Resistivity (10<sup>x</sup> ohms/square): -  
High Volt, Low Current Arc Resis (D495): -

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 1991-05-14  
Last Revised: 2018-12-20

© 2020 UL LLC



IEC and ISO Test Methods				
Test Name	Test Method	Units	Thk (mm)	Value
Flammability	IEC 60695-11-10	Class (color)	1.5	HB, HB75 (ALL)
			3.0	HB, HB40 (ALL)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	°C	-	-
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	°C	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	°C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	°C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m <sup>2</sup>	-	-
ISO Izod Impact	ISO 180	kJ/m <sup>2</sup>	-	-
ISO Charpy Impact	ISO 179-1	kJ/m <sup>2</sup>	-	-