

TEIJIN LIMITED RESIN AND PLASTIC

ENVIRONMENT QUALITY ASSURANCE DEPT, DIV 2, KASUMIGASEKI COMMON GATE, WEST TOWER, 2-1, KASUMIGASEKI 3-CHOME, CHIYODA-KU TOKYO 100-8585 JP

MN-4800(##)

Polycarbonate (PC) "Panlite", furnished as pellets

| <u>Color</u> | <u>Min. Thk</u> <u>(mm)</u> | <u>Flame</u> <u>Class</u> | <u>HWI</u> | <u>HAI</u> | <u>RTI</u> <u>Elec</u> | <u>RTI</u> <u>Imp</u> | <u>RTI</u> <u>Str</u> |
|--|--------------------------------|------------------------------|--|------------|---------------------------|--------------------------|--------------------------|
| ALL | 1.5 | V-0 | 2 | 3 | 130 | 125 | 130 |
| | 2.0 | V-0 | 2 | 3 | 130 | 125 | 130 |
| | 3.0 | V-0 | 1 | 3 | 130 | 125 | 130 |
| Comparative Tracking Index (CTI): 3 | | | Inclined Plane Tracking (IPT) kV: - | | | | |
| Dielectric Strength (kV/mm): - | | | Volume Resistivity (10 ^x ohm-cm): - | | | | |
| High-Voltage Arc Tracking Rate (HVTR): - | | | Surface Resistivity (10 ^x ohms/square): - | | | | |
| Dimensional Stability (%): - | | | High Volt, Low Current Arc Resis (D495): - | | | | |
| (##) - May be suffixed with one or two letters except for a single letter U, V or Z or the letters U, V or Z followed by another letter. | | | | | | | |

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2010-06-07

Last Revised: 2017-05-30

© 2020 UL LLC



| IEC and ISO Test Methods | | | | |
|--------------------------------|-----------------|-------------------|----------|-----------|
| Test Name | Test Method | Units | Thk (mm) | Value |
| Flammability | IEC 60695-11-10 | Class (color) | 1.5 | V-0 (ALL) |
| | | | 2.0 | V-0 (ALL) |
| | | | 3.0 | V-0 (ALL) |
| Glow-Wire Flammability (GWFI) | IEC 60695-2-12 | °C | 1.5 | 960 |
| | | | 2.0 | 960 |
| Glow-Wire Ignition (GWIT) | IEC 60695-2-13 | °C | 1.5 | 850 |
| | | | 2.0 | 850 |
| IEC Comparative Tracking Index | IEC 60112 | Volts (Max) | - | - |
| IEC Ball Pressure | IEC 60695-10-2 | °C | - | 125 |
| ISO Heat Deflection (1.80 MPa) | ISO 75-2 | °C | - | - |
| ISO Tensile Strength | ISO 527-2 | MPa | - | - |
| ISO Flexural Strength | ISO 178 | MPa | - | - |
| ISO Tensile Impact | ISO 8256 | kJ/m ² | - | - |
| ISO Izod Impact | ISO 180 | kJ/m ² | - | - |
| ISO Charpy Impact | ISO 179-1 | kJ/m ² | - | - |