



Innovative Materials Shift the Future

TIANJIN BOYUAN NEW MATERIALS CO., LTD.

Tel: +86-22-83711776/23859962

Fax: +86-22-83711387

E-mail: BHLT@boyuanmaterials.com

www.boyuanmaterials.com

Adhesion Reinforcing Primer/B3325

1.Product introduction

It is a kind of water based primer which was especially for film/sheet adhesion reinforcing. It can improve surface performance and ensure excellent adhesion between the coating and the base material.

2.Usage method

Should be adjusted based on your own process (Please call for further information).

3.Technical Characteristics

- Suitable for UV ink,excellent adhesion, especially on PP
- Good smoothness with excellent scratch resistance
- Excellent water resistance and temperature resistance

4.Parameters

Item	Parameters
Appearance	Milky white liquid
Solid Content	45±2%
PH	7~9
Adhesion	Tearing the coating with the tape does not break away from the film

5.Packing

20kg/barrel(can be adjusted according to your requirement)

6.Storage conditions and shelf life

Keep in a cool place,suggest temperature 10℃~30℃, Shelf life one year under normal storage conditions.

7.Notice

1. Suitable for roller and spray coating.
2. The film should be corona.
3. Suggest drying for 2~4 minutes in 60~70℃.

! The information is based on our practical production and result of testing. We suggest testing should be necessary before a batch use.We announce that the specification can not be used as the guarantee of the products.