



Innovative Materials Shift the Future

TIANJIN BOYUAN NEW MATERIALS CO., LTD.

Tel: +86-22-83711776/23859962

Fax: +86-22-83711387

E-mail: [BHLT@boyuanmaterials.com](mailto:BHLT@boyuanmaterials.com)

[www.boyuanmaterials.com](http://www.boyuanmaterials.com)

## RFID Tape/B6010

### ◆ Brief Introduction:

BOYUAN RFID Tape B6010 is one kind of no substrate pressure sensitive tape which is designed and developed for anti-Counterfeiting RFID label. The bonding and aging performance is excellent on variety of materials such as plastic and metal etc.

### ◆ Structure:

Structure	Composition	Color	Thickness(μm)
Release Liner(A)	PET release liner	Clear	50±3
Glue Layer	Polyacrylate	Clear	25±3
Release Liner(B)	PET release liner	Clear	27±3

### ◆ Technical Parameters:

Item	Standard	Data
Tackness(rolling ball)	GB/T 4852-2002	≥3#
Peel Adhesion (N/25mm)	GB/T 2792-2014 (50μmPET)	≥15
Static Shear Adhesion (1Kg 1h, mm)	GB/T 4851-2014	≤1.5

### ◆ Packing:

Outer: Carton      Inner: PE bag

### ◆ Storage:

Keep package sealed, 0~25°C, ≤60% RH, Avoid direct sunlight.

Shelf life: one year.

### ◆ Notice:

Gentle load, No press.

In order to avoid overflow and poor bonding strength please choose the proper parameters according to your machine setting.

---

! The information is based on our practical production and result of testing. We suggest testing should be necessary before a batch use. We announce that the specification can not be used as the guarantee of the products.