

# Backhoe Loader



## WZ30-25



### Optional Accessories

- Engine: **CUMMINS**(4BT3.9-C100,75 kW)
- Quick Hitch
- Air Conditioner inside Cab



Digging Height: 5280 mm



Side Shift Boom



Safety Lock Outrigger

### Main Technical Parameter

| Excavator Part          |                     | Loader Part          |                           |
|-------------------------|---------------------|----------------------|---------------------------|
| Bucket Volume           | 0.1 m <sup>3</sup>  | Rated Load           | 2500 kg                   |
| Bucket Width            | 650 mm              | Bucket Volume        | 1.2 m <sup>3</sup>        |
| Max. Digging Depth      | 3000 mm             | Bucket Width         | 2000 mm                   |
| Max. Digging Height     | 5280 mm             | Dumping Height       | 3500 mm                   |
| Max. Digging Radius     | 4800 mm             | Dumping Reach        | 1000 mm                   |
| Max. Boom Slewing Angle | <b>270°</b>         | Mini. Turning Radius | 5500 mm                   |
| Diesel Engine           |                     | Transmission & Drive |                           |
| Brand                   | <b>YUNNEI</b>       | Transmission         | Automatic, 4F+4R          |
| Model                   | YN38GBZ             | Torque Converter     | YJ280                     |
| Power/Speed             | 76 kW/ 2400 rpm     | Drive                | 4 x4                      |
| Type                    | 4102, Turbo-charged | Axle                 | Medium Hub Reduction Axle |
| Brake & Tyre            |                     | Dimension & Weight   |                           |
| Service Brake           | Air Cap Oil         | Total Weight         | 5800 kg                   |
| Parking Brake           | Negative Hydraulic  | Wheelbase/ Tread     | 2550 /1570 mm             |
| Tyre                    | 16/70-20            | Overall Dimension    | 6800x2100x3100 mm         |

**Container Loading Plan: 2 Sets Per 40HQ**