


OSSH



Application : Shroud

- Provide means of protection for additional IP and corrosion
- Material : PCP(CR70) or PVC
- Thermal endurance tested (-67°C ~ 130°C)

Item data sheet

(* in mm)

Part No.	A			B			D		
	D	d	L	D	d	L	D	d	L
OSSH- 16	28	6	93	24	4	52	25	4	93
OSSH- 20	35	10	98	28	7	55			
OSSH- 25	40	14	102	32	12	59			
OSSH- 32	50	18	115	40	15	65			
OSSH- 40	60	24	124	50	21	71			
OSSH- 50	74	30	132	60	28	79			
OSSH- 63	83	41	150	78	30	111			
OSSH- 63X	89	38	152						
OSSH- 75	101	54	170						
OSSH- 75X	107	53	171						
OSSH- 90	121	72	175						
OSSH- 100	131	86	190						
OSSH- 115	141	96	220						

Order Example

Part No.	Material
OSSH-A-16	PVC

SELECTION CHART

GLAND SIZE	E1WF, E1WF/LS, E1XF, OSNJ-CW, E1W/LS, E1X	OSCU, OS-E1UF, OS-E1UF/LS, E1U, E1U/LS	OSNJ-A2F, OSNJ	OSNJ-A2FF, OSNJ-A2FD, OSNJ-F, OSNJ-D	OS-A2F-U, OSNU	OS-A2F-UF, OS-A2F-UD, OSNU-F, OSNU-D
16	OSSH-A-16	OSSH-A-16	OSSH-B-16	OSSH-D-16	OSSH-B-16	OSSH-D-16
16X					OSSH-B-16	OSSH-D-16
20	OSSH-A-20	OSSH-A-20	OSSH-B-20	OSSH-A-16	OSSH-B-20	OSSH-A-16
25	OSSH-A-25	OSSH-A-25	OSSH-B-25	OSSH-A-20	OSSH-B-25	OSSH-A-20
32	OSSH-A-32	OSSH-A-32	OSSH-B-32	OSSH-A-25	OSSH-B-32	OSSH-A-25
40	OSSH-A-40	OSSH-A-40	OSSH-B-40	OSSH-A-32	OSSH-B-40	OSSH-A-32
50	OSSH-A-50	OSSH-A-50	OSSH-B-50	OSSH-A-40	OSSH-B-50	OSSH-A-40
63	OSSH-A 63	OSSH-A 63	OSSH-B-63	OSSH-A-50	OSSH-B-63	OSSH-A-50
63X		OSSH-A 63X			OSSH-B-63	OSSH-A-50
75	OSSH-A 75	OSSH-A 75	OSSH-A-63	OSSH-A-63	OSSH-A-63	OSSH-A-63
75X		OSSH-A 75X			OSSH-A-75X	OSSH-A-75X
90	OSSH-A-90	OSSH-A-90	OSSH-A-75	OSSH-A-75	OSSH-A-75	OSSH-A-75
100	OSSH-A-100	OSSH-A-100	OSSH-A-90	OSSH-A-90	OSSH-A-90	OSSH-A-90
115		OSSH-A-115			OSSH-A-100	OSSH-A-100