



JFID-FE Total Hydrocarbon Analyzer



JCT
Analysentechnik

APPLICATION

- Continuous analysis of Total Hydro Carbons (THC/VOC), e.g. at:
 - Emission monitoring
 - Safety monitoring LEL
 - VOC monitoring
 - Scrubber efficiency
 - Process gas analysis
 - Leak detection
 - Solvent recovery
 - Abatement equipment
 - Carbon absorbers
 - Coating process control
 - Monitoring of purity in O₂, N₂, Ar, H₂, CO₂





BENEFITS

- No sample conditioning system
- Quick analyzing results
- Response time < 1 sec
- Low maintenance
- Maintenancefree pump system
- Independent of pressure fluctuation

FEATURES

- Proven heated FID (Flame Ionization Detector)
- For Safe area or Ex Area Zone 1 or 2
- Fast response time
- Automatic start-up
- Automatic calibration with span check
- Automatic flame ignition
- Automatic fuel shut-off
- Electronic flow control
- Simultaneous display in ppm and mg/m³
- Integrated combustion and zero air
- Heated corrosion proof detector
- Complete diagnostics of all utilities
- Remote control and remote service

TECHNICAL DATA

Model	JFID-FE Safe area	JFID-FE EEx p zone 1	JFID-FE Ex pz 2/3 G zone 2
Description			
Operation			
Vacuum system	injectors		
Measurement range	0.5 mg org. C/m ³ to 100000 mg org. C/m ³		
Detection limit	< 0.01 mg org. C/m ³		
Linearity	< 4 % over measurement range		
Selectable units	ppm, mg/m ³ , Vol%, %LEL		
Signal output	0/4 to 20 mA; burden 600Ω not galvanically isolated		
Ambient temperature	-5 °C to 40 °C		
Response time (T ₉₀)	< 0.5 s if measured value > 20 mg org.C/m ³ < 5.0 s if measured value < 20 mg org.C/m ³		
Sample gas (self-drawn)	approx. 25 l/h with 1013 hPa optionally approx. 2 l/h; 5 l/h; 60 l/h		
Sample gas pressure	800 to 1600 mbara	800 to 1100 mbara	
Air humidity	< 90 % rel. humidity, + 20 °C < 50 % rel. humidity, + 40 °C		
Geographical altitude	0 to 1500 m above NN		
Construction			
Dimensions over all (W x H x D) [mm]	470 x 505 x 410 (IP54) 500 x 505 x 410 (IP65)	625 x 540 x 410	570 x 590 x 410
Weight	28 kg (IP54) 33,5 kg (IP65)	41 kg	38 kg
Detector temperature	adjustable up to 200 °C		
Catalyst temperature	400 °C		
Utilities			
Instrument air	3.0 to 3.9 bar, < 2 Nm ³ /h quality to ISO8573-1 1.2	3.0 to 3.9 bar, < 2 Nm ³ /h for prepurge 3.5 Nm ³ /h for normal operation 0.8 Nm ³ /h quality to ISO8573-1 1.2.1	
Fuel gas	hydrogen 0.7 to 1.0 bar, < 80 ml/min quality 5.0		
Combustion air	with internal catalyst or optional Synthetic air 1.0 to 1.5 bar, < 30 NI/h	Synthetic air 1.0 to 1.5 bar < 30 NI/h	
Calibration gas	2.0 to 2.5 bar, < 130 NI/h during calibration concentration 60 % to 80 % of the measurement range in relation to C ₃ H ₈		
Zero gas	with internal catalyst or optional Nitrogen 2.0 to 2.5 bar, < 130 NI/h quality 5.0	synthetic air 2.0 to 2.5 bar or nitrogen 2.0 to 2.5 bar, < 130 NI/h quality 5.0	
Protection class	IP 54 optional IP65	IP65	
Type of protection		 II 2G Ex px II T2-T4  II 2G Ex px IIC T2-T4 Gb  II 2G Ex d IIV	 II 2/3G Ex pz IIC T2-T4 Gc
Approvals / Signs	CE	BVS 09 ATEX E 119 X, BVS 09 ATEX E 108 U CE	BVS 09 ATEX E 144 X (2014/34/EU) CE
Electrics			
Power supply	115 V ± 10 % or 230 V ± 10 %; 48 Hz to 62 Hz		
Power consumption with supplementary heating system	< 250 W < 1000 W		

ORDER CODE

Part number	Description
207.020000	JFID-FE IP54
207.021000	JFID-FE IP65
207.021001	JFID-FE IP65 with Vortex cooler
207.021100	JFID-FE II 2G Ex px II T2-T4 zone 1, IP65
207.021200	JFID-FE Ex pz 2/3 G zone 2, IP65


Standard included for systems for Zone 1 or 2

407.950033	Status- and alarmboard with 4 x 0/4 to 20 mA output, galvanically isolated
407.020048	Conversion kit for external zero air

Options

407.950033	Status- and alarmboard with 4 x 0/4 to 20 mA output, galvanically isolated
407.040203	Dilution probe 1:10 / 1:20 heated without enclosure
207.930000	Inlinestripper (safe area)
407.030103	Flame trap ATEX
407.020047	Conversion kit for external zero air
407.020048	Conversion kit for external zero air and synthetic air for burner air
407.970081	Multi sampling MSU-block HT-4 for model "FE" (Safe area)
407.970082	Multi sampling MSU-block HT-8 for model "FE" (Safe area)
407.970083	Multi sampling MSU-block HT-4 steam for model "FE" (safe area) without fitting
407.970084	Multi sampling MSU-Block HT-8 steam for model "FE" (safe area) without fitting
407.040204	Heated 2/3 way valve, max. 180 °C
907.050000	Vortex cooler safe area
615.012001	Vortex cooler ATEX
407.040190	Air pressure regulator with fine filter assembly
DAS 2	Instrument air purifier
DM003 P	Instrument air purifier for Ex area
407.040182	Gas bottle pressure regulator for hydrogen
407.040183	Gas bottle pressure regulator for calibration gas
407.040184	Gas bottle pressure regulator for nitrogen

Gas Sampling **Probes**



Heated Sample **Lines**



Sample Gas **Coolers**



JCT
Analysentechnik

Gas Conditioning **Systems**



NOx **Converter**



and **solutions** for



JCT Analysentechnik GmbH ■ Werner Heisenberg-Strasse 4 ■ 2700 Wiener Neustadt ■ AUSTRIA ■ T +43 2622 87201 ■ sales@jct.at