



WIRING DIAGRAM		
Connector (D-Sub 9Pin public)	Signal	Color
1	Vcc	brown
2	Hall A(out)	white
3	Hall B(out)	gray
4	Hall C(out)	yellow
5	GND	green
Case	Shield	-

Cable Length (L)	Part No.	Choose the Cable Length <input checked="" type="checkbox"/>
500	HMH1812E01A1	<input type="checkbox"/>
600	HMH1812E0600	<input type="checkbox"/>
700	HMH1812E0700	<input type="checkbox"/>
800	HMH1812E0800	<input type="checkbox"/>
900	HMH1812E0900	<input type="checkbox"/>
1000	HMH1812E1000	<input type="checkbox"/>
1100	HMH1812E1100	<input type="checkbox"/>
1200	HMH1812E1200	<input type="checkbox"/>



△	Oct.08.20"	劉千予	修改Hall sensor輸出訊號	鄧朝欽
△	Jul.19.12"	王湘茹	標籤原為品號改貼圖號	張宇榮
ITEM	DATE	MODIFIED	DESCRIPTION	APPD

ROUGH % 8.0a ▽	FIT % 3.2a ▽▽	GRD 0.8a ▽▽▽	SCALE 1:X	TYPE CUSTOMER	LMAHC2	DATE Sep.09.11"	DRN 王湘茹
TOLERANCE mm				MATERIAL		CHK 黃柏盛	
UP TO	6 30	30 120	120 300	300 600	600 1200	1200 2400	2400 ± 1.5
				PART NO	HMH1M10K0300	APPD 張宇榮	
HIWIN® MIKROSYSTEM CORP.				NAME Hall sensor unit	DWG NO M10K03	A3	SHEET 1-1