



Type	L	N	Weight(kg)	Part no	Forcer type	Choosing the tpye in the table <input type="checkbox"/>
LMFC52	375	4	1.2	HM12FCD52000	LMFA52	<input type="checkbox"/>
LMFC53	536	6	1.7	HM12FCD53000	LMFA53	<input type="checkbox"/>
LMFC54	697	8	2.2	HM12FCD54000	LMFA54	<input type="checkbox"/>

ITEM	DATE	MODIFIED	DESCRIPTION	APPD
2	Oct.21.19"	黃旻章	replace 1/8"PT screw into G1/8 screw	鄧朝欽
1	Aug.19.19"	黃旻章	Zoom in on key dimensions and add height tolerances	鄧朝欽

ROUGH $\frac{M}{\%}$ 8.0a ▽	FIT $\frac{M}{\%}$ 3.2a VV	GRD 0.8a VVV	SCALE 1:X	TYPE As table	DATE May.20.19"
MACHINING PART TOLERANCE mm				CUSTOMER	DRN 黃旻章
UP TO 6	6 30 120 300 600 1200 2400	30 120 300 600 1200 2400	OVER 2400	MATERIAL	CHK 陳柏宏
±0.1	±0.2	±0.3	±0.4 ±0.5 ±0.8 ±1.0 ±1.5	PART NO.	APPD 鄧朝欽
NAME				DWG. NO	SHEET
HIWIN® MIKROSYSTEM CORP.				動子精密水冷	M19617 A3 1-1