

产品中心

地址：大连市甘井子区东海路78号

电话：0411-62658223/62658886/62658173

传真：0411-62658288

邮编：116033

国内营销中心

地址：珠海市吉大海滨南路光大国际贸易中心3006室

电话：0756-3827321/07563827322

传真：756-3827333

邮编：519015

Overseas Marketing Center

Add: No.78 Donghai Road,Gan Jingzi District Dalian,P.R.China

Tel: 0411-62658179

Fax: 0411-62658288

P.C.: 116033

样本中所有产品图片仅供参考,以实际订货产品为准。

All of the pictures in catalogues are only for your reference and subject to the actual products.

参数如有变动恕不另行通知

Parameters are subject to change without notice.

本产品由冰山松洋压缩机(大连)有限公司生产销售,本产品的产地为大连,冰山松洋压缩机(大连)有限公司。
“Panasonic”、“松下电器”和“松下”是松下控股株式会社的注册商标,基于松下控股株式会社的许可使用。

This product has been manufactured by and is sold under the responsibility of Sonyo Compressor (Dalian) Co., Ltd.,
in DaLian and Sonyo Compressor (Dalian) Co., Ltd. is the warrantor in relation to this product.

“Panasonic”, “松下电器” and “松下” are registered trademark of Panasonic Holdings Corporation and are used under
license from Panasonic Holdings Corporation.



公司网站



微信公众号



抖音号

B系列8-10HP商用涡旋压缩机 适用于商用空调冷(热)水模块机组



冰山松洋压缩机(大连)有限公司
Sonyo Compressor (Dalian) Co., Ltd.

性能特点

“小块头”“大马力”

——小壳体8、10HP产品！

- 依托B系列成熟技术。
- 更优化的电机设计。
- 出色的振动、噪声特性。
- 高可靠性轴承、增大油池容积。




基本参数

型号	冷媒	电制	功率	排气容积	制冷量	COP	噪声	注油量	重量
			HP	cm ³ /r	W	W/W	dB(A)	L	kg
5CB091SA01	R410A	50Hz/380-415V	8	91	23200	3.05	68	2.5	45
5CB110SA01	R410A	50Hz/380-415V	10	110	27400	3.05	69	2.5	45
*9CB091SA01	R32	50Hz/380-415V	8	91	24200	2.91	68	2.5	45
*9CB110SA01	R32	50Hz/380-415V	10	110	29300	3.04	69	2.5	45

初步参数。
测试条件:冷凝温度54.5°C、蒸发温度7°C、过热度11.5K、过冷度8.5K

运行范围




更宽泛的运行范围

相比传统机型，B系列8-10HP压缩机不仅在性能上达到了传统机型的水准，在运行范围上也得到了很大的拓展，最低蒸发温度可达-25°C，更加适合热泵工况下的运行

*实际运行范围以规格书为准。

结构特点



外观尺寸

单位: mm

