BOLLARD LIGHT
YZTS833

CE SASO RoHS

2W

Item NO.	YZTS833
Solar Panel	9V/3.5W Monocrystalline Solar Panel,Grade A
LED	2W,10*18mil Epistar Chip
Lifespan Of LED	More Than 50,000 Hours
Luminous Flux	220lm~240lm
Color Temperature	3000K~7500K
Beam Angle	120°
Battery	6.4V, 6AH $LiFePO_4$ Lithium Battery
Discharging Time	23h
Charging Time	8h(AM1.5,1000W/m²,25℃)
Material	6063 Aluminum, PC
Working Temperature	-25℃~55℃
Product Size	Φ255*800*Φ140*Φ195mm
Package Size	840*310*310mm
Number Of Packing	1 set/carton
Net Weight	4.7KG
Gross Weight	6KG

IK08 IP66 UV Proof Salt Spray 240hrs High-low Temp. 500hrs

Product Feature

- A Grade monocrystalline solar panel, high efficiency solar cells. Lifespan reaches more than 25 years.
- $LiFePO_4$ Lithium battery. Lifespan reaches more than 2, 000 cycles.
- Full-automatic intelligent light control.
- Branded LED chips (Bridgelux, Epistar). Lifetime up to 50, 000 hours .
- Die-casting aluminum light shell. Anti-corrosion, Anti-oxidation. High-impact PC cover.
- Easy installation, no cabling, no trenching. Labor cost saver, free maintenance.
- ≥23 working hours after fully charged.