



Soft sleeve to slide onto connectors or push into pipes, electrically conductive

Application

- industrial vacuum cleaners, vacuum cleaners

Properties

- easily and quickly fitted
- re-usable (threaded version)
- highly abrasion resistant

- microbe and hydrolysis resistant
- good resistance to oil, gasoline and chemicals
- electrically conductive wall: electrical and surface resistance $<10^3\Omega$ (according to NFPA 652 $<10^6\Omega$)
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40 °C to 90 °C
- short time to 125 °C

Design

- Wall of EC version electrically conductive $<10^3$: electrically conductive Premium Ester-Polyurethane (Pre-PUR®)

Delivery variants

- further diameters available on request
- black (standard)
- special colours: full coloured

| Rec. Adapter Ø | Rec. Adapter length | Threading depth Hose | Total Length | Weight | Suitable for Hose I.D. | Order No. |
|---|---------------------|----------------------|--------------|----------|------------------------|---------------|
| (mm) | (mm) | (mm) | (mm) | (kg/pcs) | (mm) | |
| Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345 | | | | | | |
| 38 | 44 | 40 | 85 | 0,094 | 38 | 240-0038-1003 |
| 40 | 44 | 40 | 85 | 0,087 | 40 | 240-0040-1003 |
| 50 | 49 | 41 | 90 | 0,103 | 50 | 240-0050-1003 |
| 60 | 49 | 41 | 90 | 0,133 | 60 | 240-0060-1003 |
| 70 | 52 | 44 | 96 | 0,163 | 70 | 240-0070-1003 |