



PVC hose/ tubing, fabric reinforced high pressure hose

Application

- flexible hose/ ducting for liquids and for gases
- injection moulding tool cooling, cooling water supply
- agricultural industry: irrigation, fertilizers, insecticides
- agricultural industry: high pressure spraying hose e.g. for pesticides
- industrial washing machine: washing water hose
- compressed air hose, cooling water hose, water hose
- fabric reinforced hose/ braided hose
- industrial robot, robotic, welding equipment, welding robot, welding gun: welding spot resistant hose, hose for dresspack for media as water and air
- heating hose: interior hose for media transfer

Properties

- fabric reinforced
- highly flexible
- crush resistant
- good resistance to alkalis and acids
- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -20 °C to 60 °C

Design

- NORFLEX® design
- fabric reinforced wall
- wall interior and exterior smooth
- wall: soft PVC

Delivery variants

- further diameters and lengths available on request
- black (standard)
- special colours: full coloured
- customer-specific branding

I.D.	outer Ø	Pressure	Bending Radius	Weight	Production Lengths	Order No.
(in / mm)	(mm)	(bar)	(mm)	(kg/m)	(m)	
5/16 / 8	14.00	20	26.00	0.14	50	440-9080-0500
3/8 / 10	16.00	18	45.00	0.16	50	440-9100-0500
5/8 / 16	24.00	14	92.00	0.33	50	440-9160-0500
3/4 / 19	27.00	12	116.00	0.38	50	440-9190-0500
1 / 25	34.00	10	138.00	0.54	50	440-9250-0500
1 1/4 / 32	42.00	8	234.00	0.76	50	440-9320-0500

Accessories



CLAMP 208