


Fiber Coupled Module – M9-V




Application

Pump
R&D

Features

Stabilized Wavelength
Narrow Linewidth
High Brightness
Long lifetime
Wide Wavelength Loading Range



Mserial - M9-V		Item Number ¹ EB-FCP-M9V-070-105-0976-0.5		
Parameter	Unit	Min	Type	Max
Optical²				
Center Wavelength	nm	975.5	976	976.5
Wavelength Tolerance	nm		±0.5	
Output Power ⁴	W		70	
Spectral Width (FWHM)	nm		0.5	1.0
Numerical Aperture	NA		0.17	0.18
Fiber Core	μm		105	
Fiber Connector	-	Pigtail / SMA905 (Optional)		
Fiber Length	m	2m (Optional)		
Electrical²				
Power Conversion Efficiency	%	48	50	
Slope Efficiency	W / A	6.5	6.8	
Thershold Current	A		0.6	
Operating Current	A		11.0	12.0
Operating Voltage	V		13.2	13.8
Thermal				
Operating Temperature ³	°C	15	25	35
Storage Temperature ³	°C	-40		80
Wavelength Temperature Coefficient	nm / °C		0.02	0.05
Others				
Anti Reflection Wavelength Range	nm		1030~1200	
Reflection Efficiency	dB		30	
Soldering Temperature	°C		260 (10 sec)	
Notes				
1. Explanation of Item Number: EB (Everbright In Short) - FCP (Fiber Coupled Module) - M9V (Product Serial, Wavelength Stabilized) - 070 (Output Power is 70W) - 105 (Fiber Core is 105μm) - 0976 (Center Wavelength is 976nm) - 0.5 (Wavelength Tolerance is ±0.5nm)				
2. Above Data Test at 25°C, Unless otherwise stated.				
3. Please avoid operation and storage in the condensation enviroment. If exceed operating temperature, the device lifetime will be inpacted.				
4. Lifetime reduced if exceed nominal output power.				
Version: MK04-1807B-R01				



Suzhou Everbright Photonics Co., Ltd
 Bldg 2, No. 189, Kunshanshan Road,
 Suzhou Science&Technology Town,
 Suzhou New District

www.everbrightphotonics.com
 sales@everbrightphotonics.com
 +86-512-69372570



Notice: Everbright keep improving its products to provide our customers with outstanding quality and reliability. We may change the specification and product description without notice at any time . For complete details, please contact Everbright sales representative.