



接线说明

管脚	四芯插座
1	U变频器相位
2	V变频器相位
3	W变频器相位
4	接地线 

GDK80-24Z/1.5

額定功率 1.5kW

额定电压 220V

額定轉速 24000r/min

额定频率 400Hz

额定电流 5.6A

ER-16

轴承型号	7004CX2	7001CX2
1	1	1
2	2	2
3	3	3
4	4	4
5	5	5
6	6	6
7	7	7
8	8	8
9	9	9
10	10	10
11	11	11
12	12	12
13	13	13
14	14	14
15	15	15
16	16	16
17	17	17
18	18	18
19	19	19
20	20	20
21	21	21
22	22	22
23	23	23
24	24	24
25	25	25
26	26	26
27	27	27
28	28	28
29	29	29
30	30	30
31	31	31
32	32	32
33	33	33
34	34	34
35	35	35
36	36	36
37	37	37
38	38	38
39	39	39
40	40	40
41	41	41
42	42	42
43	43	43
44	44	44
45	45	45
46	46	46
47	47	47
48	48	48
49	49	49
50	50	50
51	51	51
52	52	52
53	53	53
54	54	54
55	55	55
56	56	56
57	57	57
58	58	58
59	59	59
60	60	60
61	61	61
62	62	62
63	63	63
64	64	64
65	65	65
66	66	66
67	67	67
68	68	68
69	69	69
70	70	70
71	71	71
72	72	72
73	73	73
74	74	74
75	75	75
76	76	76
77	77	77
78	78	78
79	79	79
80	80	80
81	81	81
82	82	82
83	83	83
84	84	84
85	85	85
86	86	86
87	87	87
88	88	88
89	89	89
90	90	90
91	91	91
92	92	92
93	93	93
94	94	94
95	95	95
96	96	96
97	97	97
98	98	98
99	99	99
100	100	100

轴承润滑 油脂润滑

豊重 6KG

从轴伸端看为逆时针方向

特别警告:

1. 电主轴安装必须在装夹位置，否则易造成轴承损坏！

2. 压缩空气必须是清洁干燥的, 过滤精度0.1微米! 气压0.1-0.2MPa, 气封常开。

建议使用两级过滤, 过滤精度分别为5微米/0.1微米, 并且空气过滤器带自动排世装置。

[illegible]